

# The Effectiveness Of Liquid Waste Treatment With Tofu Industry Aeration Method

Agus Widada

*Jurusan Kesehatan Lingkungan*

*Politeknik Kesehatan Kementerian Kesehatan Bengkulu*

Bengkulu, Indonesia

agus.widada@yahoo.com

**Abstract:** *The tofu industry is processed from soy extract which mostly is a household industry producing waste with high protein and carbohydrate content. Waste produced by washing process, boiling, pressing give burden of high enough contamination because without going through the processing process before disposed of the environment. For that, it needs a pure and straightforward technology that can be utilized for the processing waste of industrial tofu. A straightforward technology that can be applied to waste treatment by combining aeration and biofilter methods to reduce levels of BOD, COD, TSS and pH improvement. Type of quasi-experiment research, pre-post test research design. The result of Kruskal Wallis statistic test showed that there was no difference of BOD, COD, TSS and pH levels on the thickness of the 10 cm, 20 cm and 30 cm excellent brick media on the 3rd, sixth and ninth days. The most effective reduction of BOD at thickness 10 cm day 6 decreased by 64.27%, decrease of COD level on the thickness of 10cm brick and 3rd day by 58,84%, decrease of TSS by day 3rdebesar 81,73%, To change pH according to the quality standard between 6 - 9, then on the thickness of brick liniment media on the sixth day has been effectively improving pH to 8.1.*

**Keywords:** *Aerationbiofilter, waste*

## I. INTRODUCTION

Environmental pollution is one of the factors that damage the environment which has an impact on living things around it. Tofu industry is one industry that produces organic waste. If this waste is channeled to the river, it will pollute the water body and if it is still used it will cause health problems<sup>1</sup>. Tofu industry waste is immediately discharged into the body of water without passing through the processing process so that it is not by the waste quality standard Permen-LH Number 15-2008 quality standard for wastewater for soybean management business/activities.

To overcome this problem, it is necessary to carry out the process of tofu wastewater treatment using a simple method to meet waste quality standards. Biofilm and aeration methods can decompose tofu waste more quickly to reduce levels of COD, BOD, TSS, and pH according to quality standards.

## II. METHOD

The type of this research was quasi-experimental research using a "pre-post test" design research design. Samples of tofu waste were taken in the industry, knowing that Tebeng Bengkulu was then included in a waste treatment tank. The sample was processed in a processing bath with a medium thickness of brick 10 cm, 20 cm and 30 cm with a volume of 90 lt. Data of BOD, COD, TSS, and pH data were examined before treatment and after treatment on the 3rd, sixth and ninth day. The research was carried out at the Poltekkes Kemenkes Bengkulu Workshop. Examination of research parameters was carried out in the laboratory of the Bengkulu City Environment Agency. The data that has been collected is then carried out by Kruskal Wallis test and presents it in narrative form and table.

## III. RESULT

This research was conducted at the Environmental Health Department Workshop (Workshop) from October to November 2016, aiming to determine the decrease in BOD, COD, TSS and pH levels in Tofu industry wastewater.

The results of measurement of BOD, CO, TSS and pH levels in various media thicknesses and contact duration are presented in table form and analyzed univariately

TABLE 1. AVERAGE BOD LEVELS BEFORE AND AFTER AERATION MOREOVER, BIOFILTRATION PROCESSES

Treatment / Thickness	Day	Concentration BOD (mg/l)	Number of decreases	% decreases
	Before Treatment	229,5	-	-
10 Cm	Third	148,5	81	35,29
	Sixth	82	147,5	64,27
	Ninth	105,5	124	54,03
20 Cm	Third	127	102,5	44,66
	Sixth	78	151,5	66,04
	Ninth	66	163,5	71,24
30 Cm	Third	141	88,5	38,56
	Sixth	85	144,5	62,96
	Ninth	121	108,5	47,28

Based on table 1, each of the BOD levels before treatment was 229.5 mg / l, the highest of the three treatments was in the treatment with a media thickness of 20 cm and the ninth day with a decrease in 71.24%.

TABLE 2. AVERAG COD LEVELS BEFORE AND AFTER AERATION MOREOVER, BIOFILTRATION PROCESSES

Treatment / Thickness	Day to-	Concentration COD (mg/l)	Number Of decreases	% decreases
	Before Treatment	362	-	-
10 Cm	Third	149	213	58,84
	Sixth	146	216	59,67
	Ninth	161	201	55,52
20 Cm	Third	128	234	64,64
	Sixth	111	251	69,34
	Ninth	107	255	70,44
30 Cm	Third	154	208	57,44
	Sixth	159	203	56,08
	Ninth	128	234	64,64

Based on table 2, each of the COD levels before treatment was 362 mg / l, so from the three treatments, the highest decrease was located in the media thickness treatment of 20 Cm on a ninth day with a percentage decrease of 70.44%.

TABLE 3. AVERAGE TSS LEVELS BEFORE AND AFTER AERATION AND BIOFILTRATION PROCESSES

Treatment / Thickness	Day	Concentration TSS (mg/l)	Number of decreases	% decreases
	Before Treatment	202,5	-	-
10 Cm	Third	37	165,5	81,73
	Sixth	39	163,5	80,74
	Ninth	23,4	179,1	88,44
20 Cm	Third	4,5	198	97,78
	Sixth	9	193,5	95,56
	Ninth	6	196,5	97,04

30 Cm	Third	158	44,5	21,98
	Sixth	18	184,5	91,11
	Ninth	14,4	188,1	92,89

Based on table 3, each level of TSS before treatment was 362 mg / l, so from the three treatments, the highest reduction was in the treatment of media thickness of 20 cm on ketide day with a percentage decrease of 97.78.

TABLE 4 AVERAGE PH BEFORE AND AFTER AERATION AND BIOFILTRATION PROCESSES

Treatment / Thickness	Day	Concentration pH (mg/l)	Number of change	% of change
	Before Treatment	4,5		
10 Cm	Third	4,8	0,3	6,67
	Sixth	8,2	3,7	82,22
	Ninth	8,1	3,6	80,00
20 Cm	Third	5,1	0,6	13,33
	Sixth	7,8	3,3	73,33
	Ninth	8,0	3,5	77,78
30 Cm	Third	6,1	1,6	35,55
	Sixth	7,8	3,3	73,33
	Ninth	8,0	3,5	77,78

Based on table 4 changes in pH at a media thickness of 10 cm, 20 cm, and 30 Cm on the sixth day had met the quality standard of limestone water with variations in pH ranging from 7.8 to 8.2.

#### IV. DISCUSSION

The results of univariate analysis, it was found that BOD levels in the treatment using variations in media thickness and length of contact found that the highest decrease in BOD levels before treatment was 229.5 mg / l, from the 3 treatments the highest reduction was in the treatment with media thickness 20 CM and the ninth day with a percentage reduction of 71.24%. The COD parameter was found that COD before treatment was 362 mg / l, so from the three treatments, the highest reduction was in the treatment of media thickness of 20 Cm on a ninth day with a percentage decrease of 70.44%. Whereas for the reduction of TSS before treatment was 362 mg / l, so from the three treatments the highest reduction was in the Treatment of media thickness of 20 cm on the third day with a percentage decrease of 97.78 and a change in pH at a media thickness of 10 Cm, 20 Cm. Moreover, 30 Cm on the sixth day had met the quality standard for wastewater with a variation of pH ranging from 7.8 to 8.2.

Some of the advantages of the wastewater treatment process with this process include: its management is straightforward, the mud produced is relatively small, can remove nitrogen and phosphorus which can cause eutrophication. The air

supply for aeration is relatively small, can be used for wastewater with a load of COD, BOD<sub>5</sub>, TSS, and pH are quite large, aeration methods are made from organic materials, are lightweight and have a high specific surface area. The higher of the specific surface area, the greater the number of microorganisms that can be attached.

The results of this research indicate that the biofilter process has a significant influence on the reduction of the parameters of BOD, COD and TSS and the improvement of pH of acidic wastewater from 4.5 to the standard pH of wastewater ranging from 6 - 9. The contact time and thickness of the media also influence the effectiveness of the biofilter in degrading organic materials in wastewater. It can be seen in the three days of contact parameters BOD, COD, TSS, and pH still do not meet the requirements. It happens because the waste load of tofu waste is quite high and requires a longer time for the degradation process by organic-eating microorganisms.

The thickness of the media also influences the reduction of BOD, COD, TSS and pH levels. The thickness of the media is related to the surface of the media surface to attach the biofilm. The more surface area of the media for biofilm attachment is more effective in reducing these parameters. With the surface area, more and more biofilms/microorganisms are doing the degradation process of organic materials in the tofu waste.

This result is by research conducted by Romayanto et al. (2006) with the title of processing domestic wastes with aeration, and the addition of *Pseudomonas putidi* bacteria can reduce BOD by 71.48%, and TSS by 90.77% with 216 hours of aeration.

## V. CONCLUSION

The results of the research that have been conducted can be concluded as follows:

1. The most effective decrease in BOD levels at 20 cm thickness on day 9 with a decrease of 71.24%.
2. The most effective decrease in COD levels at 20 cm thickness on day 9 with a decrease of 70.44%.
3. The most effective reduction in TSS levels at 20 cm thickness on the 3rd day with a decrease of 97.78%.
4. The most effective pH reduction at 10 cm thickness sixth day with a decrease of 82.22%.

This research can be used as a learning media for students, especially PAPLC courses and is an alternative waste treatment process in the community because it is quite useful in improving the quality of wastewater so that it meets the quality standards of wastewater for soybean processing activities.

For further research, particular bacteria can be developed that have a more useful ability in treating tofu wastewater.

## REFERENCES

- [1] Astuti (2007). pengolahan air limbah industri tahu dengan menggunakan teknologi plasma. Tuha Agung, R. Hanry Sutan Winata). Teknik lingkungan universitas pembangunan nasional "veteran" Jawa Timur. Jl. Ranguh Madya Gunung Anyar Surabaya. 60294.
- [2] Herlambang Ari, (2002). Teknologi pengolahan limbah cair tahu-tempe. <http://www.kelair.bppt.go.id>
- [3] Hidayah, (2007). Potensi Dan Pengaruh Tanaman Pada Pengelolaan Air Limbah Domestik Dengan Sistem Constructed Wetland. Jurnal Ilmiah Teknik Lingkungan.
- [4] Jenie, dkk, (2006). Pengolahan limbah pangan. Kanisius. Yogyakarta KLH, Kementrian Lingkungan Hidup, No 32 tahun 2009, perlindungan dan pengelolaan lingkungan hidup. <http://www.menlh.go.id>
- [5] Nurhassan&pramudyanto,(2007). Pengolahan Limbah Cair Industri Dengan 3 Metode Pengolahan.
- [6] Permen LH No 5 tahun 2014. Baku mutu air limbah/kegiatan pengelolaan kedelai. <http://widyacipta.com/file>.
- [7] Romayanto, Wiryanto dan Sajidan.2006. Pengolahan limbah domestik dengan aerasi dan penambahan bakteri *Pseudomonas putidi*. Jurnal Bioteknologi, DOI.10.13057/biotek/c030202
- [8] Sugito (2013). Aplikasi Instalasi Pengolahan Air Limbah Biofilter untuk Menurunkan Kandungan Pencemar BOD, COD dan TSS di Rumah Sakit Bunda Surabaya. Jurnal. Universitas Adi Buana. Surabaya.
- [9] Said Nusa Idaman , (1999). Teknologi pengolahan air limbah tahu-tempe dengan proses biofilter anaerob dan aerob. Kelompok teknologi pengolahan air bersih dan limbah cair Direktorat teknologi lingkungan, Deputi bidang teknologi informasi, energi, material, dan lingkungan badan pengkajian dan penerapan teknologi. Jakarta.
- [10] ----- (2005). Aplikasi Bio-Ball Untuk Media Biofilter Studi Kasus Pengolahan Air Limbah Pencucian Jean. JA Vol : 1 (2005), Jakarta.
- [11] -----(2010). Pengelolaan air limbah dengan proses biofilter tercelup. BPPT. Jakarta.
- [12] ----- (2005). Uji Performance Biofilter Anaerobik Unggun Tetap Menggunakan Media Biofilter Sarang Tawon Untuk Pengolahan Air Limbah Rumah Potong Ayam. Kelompok Teknologi Pengelolaan Air Bersih dan Limbah Cair, Pusat Pengkajian dan Penerapan Teknologi Lingkungan, BPPT. Jurusan Kimia, Universitas Negeri Jakarta
- [13] Tjokrokusumo (2009).Pengantar Khusus Pengelolaan YLH. Yogyakarta.
- [14] Konsep Teknologi Bersih danPengolahan Air. STTL
- [15] Sugiharto, (2008). Dasar-Dasar Pengelolaan Air Limbah. Universitas Indonesia Jakarta.







